



Zoning Resolution

THE CITY OF NEW YORK

Eric Adams, Mayor

CITY PLANNING COMMISSION

Daniel R. Garodnick, Chair

23-47 - Minimum Required Rear Yards

File generated by <https://zr.planning.nyc.gov> on 5/20/2024

23-47 - Minimum Required Rear Yards

LAST AMENDED

4/30/2008

R1 R2 R3 R4 R5 R6 R7 R8 R9 R10

In all districts, as indicated, a rear yard with a depth of not less than 30 feet shall be provided at every rear lot line on any zoning lot except as otherwise provided in Sections [23-52](#) (Special Provisions for Shallow Interior Lots), [23-53](#) (Special Provisions for Through Lots) or [23-54](#) (Other Special Provisions for Rear Yards). Rear yards shall also be provided along portions of side lot lines as set forth in Section [23-471](#) (Beyond one hundred feet of a street line).

23-471 - Beyond one hundred feet of a street line


LAST AMENDED

4/30/2008

R1 R2 R3 R4 R5 R6 R7 R8 R9 R10

In all districts, as indicated, for interior or through lot portions of corner lots, and for zoning lots bounded by two or more streets that are neither corner lots nor through lots, the portion of a side lot line beyond 100 feet of the street line that it intersects shall be considered a rear lot line and the following rules shall apply along such rear lot line :


- (a) In all districts, a rear yard with a minimum depth of 30 feet shall be provided where such rear lot line coincides with a rear lot line of an adjoining zoning lot.



CORNER LOT

(23-471a)

- (b) In R1 through R5 Districts, a rear yard with a minimum depth of eight feet shall be provided where such rear lot line coincides with a side lot line of an adjoining zoning lot.



ZONING LOT BOUNDED BY TWO OR MORE STREETS

(NEITHER A CORNER LOT NOR A THROUGH LOT)

(23-471b)

- (c) In R6 through R10 Districts, no #rear yard# shall be required where such #rear lot line# coincides with a #side lot line# of an adjoining #zoning lot#.