



Zoning Resolution

THE CITY OF NEW YORK
Zohran K. Mamdani, Mayor

CITY PLANNING COMMISSION
Sideya Sherman, Chair

23-732 - Floor area ratio and open space ratio in R6 through R9 Districts

File generated by <https://zr.planning.nyc.gov> on 5/28/2026

23-732 - Floor area ratio and open space ratio in R6 through R9 Districts

LAST AMENDED

12/5/2024

R6 R7 R8 R9

In the districts indicated without a letter suffix, for #sky exposure plane buildings#, the minimum required #open space ratio# and the maximum #floor area ratio# for any #zoning lot# shall be determined by the #height factor# of such #zoning lot# as set forth in this Section. Where elected, such #floor area ratio# shall supersede the #floor area ratio# provisions of Section [23-22](#), and apply to all #residences#, including #qualifying affordable housing# or #qualifying senior housing#.

The minimum #open space# required through the application of a minimum #open space ratio# shall be applied in conjunction with the applicable regulations of Section [23-30](#) (YARDS, COURTS AND OTHER OPEN AREA REGULATIONS). The obstructions set forth in Section [23-311](#) shall be permitted in required #open space#.

MINIMUM REQUIRED OPEN SPACE RATIO AND MAXIMUM FLOOR AREA RATIO

R6 through R9 Districts

For #zoning lots# with a #height factor# of	In R6 Districts		In R7 Districts		In R8 Districts		In R9 Districts	
	Min. Req. #Open Space Ratio#	Max. #Floor Area Ratio#	Min. Req. #Open Space Ratio#	Max. #Floor Area Ratio#	Min. Req. #Open Space Ratio#	Max. #Floor Area Ratio#	Min. Req. #Open Space Ratio#	Max. #Floor Area Ratio#
1	27.5	0.78	15.5	0.87	5.9	0.94	1.0	0.9

2	28.0	1.28	16.0	1.52	6.2	1.78	1.4	1.9
3	28.5	1.62	16.5	2.01	6.5	2.51	1.8	2.8
4	29.0	1.85	17.0	2.38	6.8	3.14	2.2	3.6
5	29.5	2.02	17.5	2.67	7.1	3.69	2.6	4.4
6	30.0	2.14	18.0	2.88	7.4	4.15	3.0	5.0
7	30.5	2.23	18.5	3.05	7.7	4.55	3.4	5.6
8	31.0	2.30	19.0	3.17	8.0	4.88	3.8	6.1
9	31.5	2.35	19.5	3.27	8.3	5.15	4.2	6.5
10	32.0	2.38	20.0	3.33	8.6	5.38	4.6	6.8
11	32.5	2.40	20.5	3.38	8.9	5.56	5.0	7.0
12	33.0	2.42	21.0	3.41	9.2	5.71	5.4	7.3
13	33.5	2.43	21.5	3.42	9.5	5.81	5.8	7.4
14	34.0	2.43	22.0	3.44	9.8	5.92	6.2	7.5
15	34.5	2.43	22.5	3.42	10.1	5.95	6.6	7.5
16	35.0	2.42	23.0	3.41	10.4	5.99	7.0	7.5
17	35.5	2.42	23.5	3.40	10.7	6.02	7.4	7.5

18	36.0	2.40	24.0	3.38	11.0	6.02	7.8	7.4
19	36.5	2.39	24.5	3.36	11.3	6.02	8.2	7.4
20	37.0	2.38	25.0	3.33	11.6	6.02	8.6	7.3
21	37.5	2.36	25.5	3.30	11.9	5.99	9.0	7.2

For #zoning lots# with #height factors# greater than 21, the minimum required #open space ratio# shall be as set forth in the following table:

OPEN SPACE RATIO FOR HIGH BUILDINGS

District	Minimum Required #Open Space Ratio# at #Height Factor# of 21	Additional Required #Open Space Ratio# for each Additional #Height Factor#
R6	37.5	0.5
R7	25.5	0.5
R8	11.9	0.3
R9	9.0	0.4

For these #zoning lots#, the maximum #floor area ratio# shall be such as can be attained at the required #open space ratio# for the #height factor#.*

* The #floor area ratio# attainable at a given #height factor# and a given #open space ratio# may be computed from the following formula:

$$\frac{1}{FAR} = \frac{OSR}{100} + \frac{1}{HF}$$