



## **Zoning Resolution**

**THE CITY OF NEW YORK**  
**Zohran K. Mamdani, Mayor**

**CITY PLANNING COMMISSION**  
**Sideya Sherman, Chair**

# **141-23 - Special Height and Setback Regulations Along the Elevated Rail Structure Outside Subdistrict A**

File generated by <https://zr.planning.nyc.gov> on 6/21/2026

---

## 141-23 - Special Height and Setback Regulations Along the Elevated Rail Structure Outside Subdistrict A

---

LAST AMENDED

12/5/2024

For #zoning lots#, or portions thereof, within 100 feet of #street lines# along the elevated rail structure on Jerome or River Avenues, and located outside Subdistrict A, the underlying height and setback provisions are modified by the provisions of this Section.

(a) #Street wall# location

The #street wall# location provisions of paragraph (a)(1) of Section [35-643](#) (Special provisions in other geographies) shall apply.

Any open space between a #street wall# and a #street line# along the elevated rail structure on Jerome or River Avenues shall comply with the special open space provisions of paragraph (a) of Section [141-32](#).

(b) Base heights, maximum #building# heights

The underlying height and setback provisions of Section [35-63](#) (Height and Setback Requirements in Commercial Districts with R6 Through R12 Equivalency), inclusive, shall apply, as modified by the provisions of paragraph (a) of Section [35-643](#) (Special provisions in other geographies). However, for #street walls# facing the elevated rail structure, beyond 75

feet of the corner of #streets# intersecting Jerome or River Avenues, the maximum base height shall be 30 feet.

(c) Required and permitted articulation

For #street walls# fronting the elevated rail structure on Jerome or River Avenues with widths exceeding 100 feet, a minimum of 20 percent of the surface area of such #street walls# above the level of the second #story#, or a height of 30 feet, whichever is lower, shall either recess or project a minimum of three feet from the remaining surface of the #street wall#. Any such projections shall be considered a permitted obstruction into a required setback, and the depth of such projections along the elevated rail structure shall not exceed three feet.

In addition, the underlying dormer provisions of paragraph (b) of Section [23-413](#) (Permitted obstructions in certain districts) shall be modified for portions of #buildings# facing the elevated rail structure, so that above the maximum base height set forth in paragraph (b) of this Section, dormers shall be permitted only within 75 feet of a corner.