



Zoning Resolution

THE CITY OF NEW YORK

Eric Adams, Mayor

CITY PLANNING COMMISSION

Daniel R. Garodnick, Chair

146-20 - SPECIAL BULK REGULATIONS

File generated by <https://zr.planning.nyc.gov> on 7/22/2025

146-20 - SPECIAL BULK REGULATIONS

LAST AMENDED
5/28/2025

The #bulk# regulations of the underlying districts or of Article XII, Chapter 3 (Special Mixed Use District) shall apply, except as modified by the provisions of this Section, inclusive.

146-21 - Floor Area Regulations

LAST AMENDED
5/28/2025

146-211 - Floor area modifications for certain paired districts

LAST AMENDED
5/28/2025

In M1A Districts paired with #Residence Districts#, for #zoning lots# with #buildings# containing #residential# and non-#residential uses#, notwithstanding the maximum #floor area ratio# for individual #uses# on the #zoning lot#, the total #floor area ratio# shall be as follows:

TOTAL FLOOR AREA RATIO

District	Total #floor area ratio#
M1-1A/R6B	3.0
M1-2A/R6A	5.0

146-22 - Special Yard Regulations

LAST AMENDED
5/28/2025

The #yard# regulations of the underlying districts shall apply, except that for #zoning lots# where the #side lot line# is located within 30 feet of an elevated rail line, the #rear yard# and #rear yard equivalent# provisions of Section [23-34](#) (Rear Yard and Rear Yard Equivalent Requirements), inclusive, need not apply.

146-23 - Special Height and Setback Regulations

LAST AMENDED
5/28/2025

146-231 - Street wall modifications

LAST AMENDED
5/28/2025

For #zoning lots#, or portions thereof, fronting on Atlantic Avenue or Bedford Avenue, the applicable #street wall# location regulations shall be modified as follows:

- (a) the #street wall# shall be located at least 20 feet beyond the curb of the sidewalk, except that such depth need not exceed five feet from the #street line#;
- (b) for #developments# with #building# widths exceeding 100 feet, a minimum of 20 percent of the surface area of such #street walls# above the level of the second #story#, or a height of 30 feet, whichever is lower, shall either recess or project a minimum of three feet from the remaining surface of the #street wall#; and
- (c) for the purposes of applying the provisions of Section [35-633](#) (Additional height and setback provisions) on shallow #through lots# with a frontage along Atlantic Avenue, the #street wall# location requirements of this Section shall be required along Atlantic Avenue.

146-232 - Other height and setback modifications

LAST AMENDED
5/28/2025

The height and setback regulations of the applicable underlying districts shall be modified as follows:

- (a) for #zoning lots#, or portions thereof, within 100 feet of a #side lot line# that is located within 30 feet of an elevated rail line, the applicable maximum #building# heights may be increased by 10 feet in M1-2A/R6A Districts, and by 20 feet in C6-3A and M1-4A/R9A Districts; and
- (b) in M1A Districts paired with #Residence Districts#, for #zoning lots# with #buildings# containing both #residential# and non-#residential uses#, the following height and setback modifications may be applied:

District	Maximum base height (in feet)	Maximum height of #buildings or other structures# (in feet)
M1-1A/R6B	95	
M1-2A/R9A	125	

In addition, for #zoning lots# with a #lot area# greater than or equal to 20,000 square feet, a #building# may exceed the maximum #building# heights established in such table by 25 percent.